

Impact 3342 Plus

Dotmatrix Printer



A reliable compact printer that delivers high print quality at speed up to 600 cps.

- > High Quality LQ Printer
- > Full Arabic Support
- > High Speed Dotmatrix

Impact 3342 Plus provides advanced paper handling to support the largest variety of papers. It is ideally suited for business and industrial working environments where reliability, speed and quality are critical factors.

Reliable mechanism

The Impact 3342 Plus features an advanced tractor mechanism that allows flexible paper manipulation from: front in/top out, rear in/top out and from bottom in/top out.

It comes standard with a powerful 24-pin print head that functions on different types of paper using a wide range of fonts, character sets and barcodes.

Outstanding performance

The Impact 3342 Plus printer is designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as well as on multiple copy forms up to 1+5 copies.



Key Features

- > Print speed up to 600 cps
- > 400 million strokes per wire print head life
- > Up to 360 x 360 dpi print resolution
15 million characters ribbon life
- > Up to 6 copies
- > Up to 128 KB input buffer
- > 25,000 hours MTBF
- > Advanced paper handling for troublefree use of continuous forms
- > Standard Parallel and USB interfaces
Integrated Ethernet LAN (optional)
- > Ideally designed for Continuous forms, Adhesive slip, Multicopy parts
- > Available with built-in Arabization for full Arabic standard support



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae

Technical Specifications Impact 3342 Plus

Print Technology

24-pin, serial impact dotmatrix

Bilingual print speed

	10 cpi	12 cpi
Super High Speed	600 cps	-
HSD	480 cps	540 cps
Draft	360 cps	435 cps
LQ	120 cps	145 cps

Character Sets/Arabic Code Page

Host codesets: ASMO-449/449+, ASMO-708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, X BASIC, CODAR-UFD, ICL, CODAR, ICL ASMO-708, HP Arabic-8, Integro 708 UNIX, ASMO/French, French/ASMO, User-defined.

PC code sets: ADOS-708/ 709/ 710/ 711/ 720/ 864, Arabic Windows 1256, IBM437, IBM851, IBM864

Operating Mode Support

8-bit Arabic with neutrals, GLCCs, & GLCCs balancing ; 7-bit Arabic with GLCCs, GLCCs balancing, & escape sequences

Fonts

Arabic Fonts Naskh Draft, Naskh NLQ

Latin Fonts Draft, Roman, Sans Serif, OCR-A, OCR-B, etc.

Bar Codes

8 types including EAN-13, Code 39, Code 128

Print Characteristics

Width (cut sheet): 148 – 420 mm

Continuous paper: 101-06 mm

Length (cut sheet): up to 364 mm

Thickness: 0.065 to 0.52 mm

Number of Copies

Original + 5



Energy Conservation Certified
Energy Star Conformed

Print Resolution

Up to 360 x 360 dpi

Number of Columns

136 col.

Paper Insertion

Continuous: Front in/ Top Out
Rear in/Top Out Bottom in/Top out

Emulation

Epson LQ ESC/ P2, IBM, OKI

Interface and connectivity

Standard: USB + Serial + Parallel, Ethernet (optional)

Input Data Buffer

Up to 128 Kb

Consumables

Type: Black ribbon cartridge

Life: 15 million characters

Print head life

400 million strokes per wire

MTBF

25,000 hours

Physical

Dimensions (w x d x h): 623 x 395 x 173 mm

Weight: 13 kg

Operating Environment

Temperature: Operating: 5 to 35 degrees C

Storage: -20 to 60 degrees C

Humidity: 20% to 80% (operating)

Consumptions: 15W to 75W

Voltage: 220 v, / 110 v ; 50/60 HZ

Drivers Support

Win 7 / Win 8 / Win 10 (32 bit /64 bit)

Warranty

Standard one-year

globalis
international

ALISTECH
اليس تك



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae