PRINTRONIX DL3850+ 24-Pin Dot Matrix Printer



High Quality. Silent Printing. Low Profile.

- > Compact, low profile 136 column design.
- > Ultra-low noise emissions 49dBA.
- >24-pin printhead for high-quality output.
- > Multiple Interface Options.

RIBBON

DL3850+ Ribbon Unit



FUJITSU
DL Series 24-pin
Dot Matrix Printers
Exclusively distributed by Printronix



Model Name		DL3850+
Printing Technology		Bi-directional with logical seeking
Print Head		24-pin, Impact Dot Matrix
Printing columns (10cpi)		136 column
Speed	Letter Quality	113cps (10cpi) ,135cps (12cpi)
	Report Quality	225cps (10cpi), 270cps (12cpi)
	Draft Quality	360cps (10cpi), 432cps (12cpi)
	High Draft Quality	448cps (10cpi), 537cps (12cpi)
Resolution		360x360dpi (Maximum Graphics Resolution, Under ESC/P Emulation only)
Copy Ability		Original+4 copies
Interface	Parallel	IEEE1284 Nibble Mode
	USB	USB Ver.1.1 TYPE B
	Serial	RS232C (25-pin)
	LAN (Optional card needed)	10/100BaseT, TCP/IP Protocol
Emulation		Fujitsu DPL24C PLUS, Epson ESC/P2, IBM †XL24E
Input Buffer		Max. 128KB
Dimension (WxDxH)		570 x 330 x 120mm (22.4x13.0x4.72inch)
Weight		Approximately 9.7Kg (19lbs)
Noise		49dBA
Reliability	MTBF	20,000H (25%duty cyde)
	MTTR	0.3H
	Printer Life	5 million Line-Feed or 5 years
Option		RS232C I/F Board
		LAN Card
Print Head	Print Head Life	400 million strokes (each pin)
Ink Ribbon	Ribbon Life (Black)	5 million characters
Model		Parallel + USB Model (LAN Upgradeable)
		Parallel + RS232C Model







Headquarters & Americas Operations





